

CRACK FILL MELTER APPLICATORS

RY10MA-V3 WITH ERGOKIT

The RY10MA was designed to be the most efficient, safe, reliable and easy-to-use torch fired crack fill machine. Contractors can melt and apply up to 400 feet per hour; 3,200 feet per day and features cutting edge innovations like the RynoValve™, Adjustable Controls, and on-the-fly agitation.



**BEST-IN-CLASS
ENTRY LEVEL**

SPECIFICATIONS

Fluid Capacity
12.5 US Gallons

Kettle Steel Thickness
14 Gauge

Assembled Dimensions
47.0" x 26.7" x 48.8"

Empty Weight
148.2 lbs / 67.4 kg

Max Capacity Weight
270.7 lbs / 123.0 kg

Fuel Type
Propane

Max Fuel Pressure
30 psi

Burner Type
150,000 BTU/hr
Heating Torch

Valve Type
1.25" RynoValve™

Agitation Type
On-the-fly

PRODUCTIVE

- Melt and apply up to 3,200 feet of crack sealant per day.
- RynoValve™ requires virtually no preheating time and is ready to use as soon as you have hot sealant in the kettle, saving you time between jobs.

RELIABLE

- The unique glycerin-filled thermometer is highly resistant to damage caused by constant vibrations during regular use, which ensures a reliable temperature reading every time.
- Rear wheels feature double ball bearings for increased stability and smooth operation.

EASY TO OPERATE

- Side-by-side controls, which include on-the-fly agitation, help the operator control agitation, flow, the application of material, view and adjust temperature, all without leaving the operating position.
- Adjustable regulator includes a pressure gauge to easily monitor fuel pressure.

SAFETY BUILT-IN

- Features a heavy-duty ratchet strap to secure the propane tank.
- Handlebars are adjustable from 35"- 42"—optimize valve squeeze distance and spring tensions to reduce operator fatigue.